

Product Specification

Product Name:	TERRAIN Rolls 8
Description:	Resilient floor covering made from 94% recycled rubber content and 100% EPDM granules, LEED® accredited floor covering used as general purpose flooring in various application, easy to clean and maintain with long durability and fatigue resistance.
Application:	Used as a floor surface to prevent general discomfort and injuries associated with repetitive motion or standing for long periods of time, generally used in Gymnasiums and fitness centers Locker rooms, Pathways and corridors, daycares, schools, library, Clubhouses, Restaurants, Exhibition halls, Warehouses and Hospitality
Color:	Available in a variety of colors, percentages and custom color blends
Dimension:	Roll good: (1.2 wide, 10 m long)
Thickness:	8mm (+/- 0.3 mm)
Roll Weight:	(100.8 kg/roll)
Roll Area:	12m ²
Rolls/Pallet:	12
Lead Time:	8-10 weeks after receipt of order

Technical Data

Wear Hardness (DIN 53577):	Approximately 4.0 MPa
Shore A Hardness (DIN 53505):	60 (+ / - 5)
Compression Set (DIN 53517):	Approximately 15%
Abrasion (DIN 53516):	Maximum 200 mm ³

Tensile Strength
(EN ISO 1798):

Approximately 1.5 N/mm²

Elongation At Break
(EN ISO 1798):

Approximately 90%

Coefficient of Friction
(EN 13893:2002):

$\mu = 0.47$ (safe)

Fire Resistance
(DIN EN 13501-1):

E_n (B2)

Light Fastness
(DIN EN 105-B02:1999-09):

2-3

Electrostatic Properties
(DIN EN 1815:1995-06):

0.5 kV

Remaining Deformation
(EN 433:1994-11):

0.13 mm

Reduction of Impact Sound Pressure Level (ΔL_w)
(DIN EN ISO 140-8:1998-03):

18 dB

Use With Wheel Chairs
(DIN EN 1307:1997-06):

For permanent use adapted