TECHNICAL DATA SHEET

TERRAC®

Acoustic Solutions by TERRAIN

TERRAC®STRENGTH

PRODUCT DESCRIPTION

The Terrac® product range is crafted to minimise both Airborne and Impact sounds in flooring systems, like speech, loud music, footsteps, and structural-borne sound. Our underlays are made from recycled SBR, aligning with our commitment to an eco-friendly environment. Our underlayment is quick and easy to install and offers excellent sound attenuation and resistance to compressive loads. It can be used beneath various surfaces, including concrete floors, beneath ceramic tiles, wood, vinyl, and more.



TECHNICAL SPECIFICATION

TEST	UNITS	VALUES
Thickness	MM	8
Roll dimension (W x L)	M	1.2 x 10
Roll Weight	Kg	93
Elongation Break	.%	52 - 73
Tear Strength	Kn/m	3.5 – 3.8
Shore A Hardness	Shore A	56
Slip Resistance	Wet pendulum	Class X
Slip Resistance	dry pendulum	Class F
Temperature	˚C	-25 to 105

*Note: Our rolls may consist of two combined sections to meet the required length, ensuring quality control.

CERTIFICATIONS

ISO 10140- 2, 10140-3

ASTM INTERNATIONAL E90, E492, E2179

UAE صنع في الإمارات MADE IN UAE

CONTACT

+971 4 263 2332 | +971 55 325 2253
inquiry@terrainfloorings.com
terrainfloorings.com