

TerraFit™ – INFINITY

ABOUT

The Terrain Infinity is the perfect blend of comfort and performance. Available in a variety of colors in an interlocking pattern for easy installation. Made of Natural and Styrene-Butadiene Rubber (NR - SBR) with an orange peel surface it allows easy cleaning.



PERFORMANCE ATTRIBUTES

- Compatible with most floor finishes.
- Fast installation.
- Natural elasticity reduces noise.
- Antistatic
- Dense and sturdy
- Multiple colour options
- Easy to clean

DIMENSIONS

- Size: 100cm x 100cm
- Thickness (mm): 7
- Standard Tolerances : Width: +/- 3 mm
Length: +/- 3mm
Thickness: +/-2m

MATERIAL

- 100% NR-SBR in a variety of colors.

TECHNICAL DATA

PROPERTY	TEST METHOD	UNITS	TEST RESULTS
Shore Hardness	ASTM D2240-97	Shore A	70 ± 5
Specific Gravity	ASTM D792	g/cm ³	1.45 ± 0.05
Tensile Strength	ASTM D412-98A	MPa	Min 9.5
Elongation at Break	ASTM D412-98A	%	Min 315
Compression Set @ 70° / 22hrs	ASTM D395-98	%	25 Max
Abrasion Loss	ASTM D5963	mm ³	344
Aging Test (70° / 22hrs)	ASTM D573-99		
Hardness Change	ASTM D2240-97	Shore A	+5 Max
Tensile Strength Change	ASTM D412-98a	%	-10 Max
Elongation @ Break Change	ASTM D 412-98a	%	-25 Max
Tear Strength	ASTM D624	KN/m	34 Min

Working temp: Up to 70°C

Good Abrasion Resistance

*The values & properties stated above are carried out in our lab for the component used in the production. However, they do not constitute a guarantee for a specific product feature & do not establish a legal contract

CERTIFICATIONS



CONTACT

+971 4 263 2332 | +971 55 325 2253
 inquiry@terrainfloorings.com
 terrainfloorings.com

