

TerraTuf™ – EDGE MATS

ABOUT

These mats are similar in design to the hollow mats, with the added advantage of lowered edges preventing any hazardous falls. They are flexible and extremely comfortable.



PERFORMANCE ATTRIBUTES

- Anti-fatigue & Anti-Slip.
- Fast installation.
- Natural elasticity reduces noise.
- Antistatic
- Easy drainage
- Trip resistant due to lowered edges

DIMENSIONS

- Size: 90x150 cm
- Thickness (mm): 13
- Type: Punched or Unpunched holes
- Weight: 11.5kgs
- Standard Tolerances : Width: +/- 3 mm
Length: +/- 3mm
Thickness: +/-2mm

MATERIAL

- Blend of NR-SBR compound
- Available in Black and other colors upon request.

TECHNICAL DATA

PROPERTY	TEST METHOD	UNITS	TEST RESULTS
Shore Hardness	ASTM D2240-97	Shore A	60±5
Specific Gravity	ASTM D792	g/cm ³	1.3±0.05
Tensile Strength	ASTM D412-98A	MPa	Min 5
Elongation at Break	ASTM D412-98A	%	Min 350
Compression Set @ 70° / 22hrs	ASTM D395-98	%	25 Max
Abrasion Loss	ASTM D5963	mm ³	200 Max

Working Temperature upto 70 °C

Good Abrasion Resistance

*The values & properties stated above are carried out in our lab for the component used in the production. However, they do not constitute a guarantee for a specific product feature & do not establish a legal contract

CERTIFICATIONS



CONTACT

+971 4 263 2332 | +971 55 325 2253
inquiry@terrainfloorings.com
terrainfloorings.com

