

### TerraFit® – INFINITY

#### ABOUT

The Terrain Infinity is the perfect blend of comfort and performance. Available in a variety of colors in an interlocking pattern for easy installation. Made of Natural and Styrene-Butadiene Rubber (NR - SBR) with an orange peel surface it allows easy cleaning.



#### PERFORMANCE ATTRIBUTES

- Compatible with most floor finishes.
- Fast installation.
- Natural elasticity reduces noise.
- Antistatic
- Dense and sturdy
- Multiple colour options
- Easy to clean

#### DIMENSIONS

- Size: 100cm x 100cm
- Thickness (mm): 7
- Standard Tolerances : Width: +/- 5 mm  
Length: +/- 5mm  
Thickness: +/-0.7mm

#### MATERIAL

- 100% NR-SBR in a variety of colors.

#### TECHNICAL DATA

PROPERTY	TEST METHOD	UNITS	TEST VALUES
Shore Hardness	ASTM D2240-97	Shore A	70 ± 5
Specific Gravity	ASTM D792	g/cm <sup>3</sup>	1.45 ± 0.05
Tensile Strength	ASTM D412-98A	MPa	Min 9.5
Elongation at Break	ASTM D412-98A	%	Min 315
Compression Set @ 70° / 22hrs	ASTM D395-98	%	25 Max
Abrasion Loss	ASTM D5963	mm <sup>3</sup>	344
Tear Strength	ASTM D624	KN/m	30 Min
Aging Test (70° / 22hrs)	ASTM D573-99		
Hardness Change	ASTM D2240-97	Shore A	± 5 Max
Tensile Strength Change	ASTM D412-98A	%	± 10 Max
Elongation @ Break Change	ASTM D 412-98A	%	-25 Max

Working temp: Up to 70°C

Good Abrasion Resistance

\*The values & properties stated above are carried out in our lab for the component used in the production. However, they do not constitute a guarantee for a specific product feature & do not establish a legal contract

#### CERTIFICATIONS



#### CONTACT

+971 4 263 2332 | +971 55 325 2253  
 inquiry@terrainfloorings.com  
 terrainfloorings.com

