

### TerraTuf® – EDGE MATS

#### ABOUT

These mats are similar in design to the hollow mats, with the added advantage of lowered edges preventing any hazardous falls. They are flexible and extremely comfortable.



#### PERFORMANCE ATTRIBUTES

- Anti-fatigue & Anti-Slip.
- Fast installation.
- Natural elasticity reduces noise.
- Antistatic
- Easy drainage
- Trip resistant due to lowered edges

#### DIMENSIONS

- Size: 90x150 cm
- Thickness (mm): 13
- Type: Punched or Unpunched holes
- Weight: 11.5kgs
- Standard Tolerances : Width: +/- 3 mm  
Length: +/- 3mm  
Thickness: +/-2mm

#### MATERIAL

- Blend of NR-SBR compound
- Available in Black and other colors upon request.

#### TECHNICAL DATA

PROPERTY	TEST METHOD	UNITS	TEST VALUES
Shore Hardness	ASTM D2240-97	Shore A	60±5
Specific Gravity	ASTM D792	g/cm <sup>3</sup>	1.3±0.05
Tensile Strength	ASTM D412-98A	MPa	Min 5
Elongation at Break	ASTM D412-98A	%	Min 350
Compression Set @ 70° / 22hrs	ASTM D395-98	%	25 Max
Abrasion Loss	ASTM D5963	mm <sup>3</sup>	200 Max

Working Temperature upto 70 °C

Good Abrasion Resistance

\*The values & properties stated above are carried out in our lab for the component used in the production. However, they do not constitute a guarantee for a specific product feature & do not establish a legal contract

#### CERTIFICATIONS



9001:2015



E648, E492, E2179  
E648, E3152-18



EN1177, EN71



DIN 3763:2022-08



#### CONTACT

+971 4 263 2332 | +971 55 325 2253  
inquiry@terrainfloorings.com  
terrainfloorings.com

