

### TerraTuf® – HAMMER TOP

#### ABOUT

Designed specifically for horse stables. These mats are solid and rugged. They provide extreme resistance to abrasion and wear and tear. The grooves at the bottom help with the drainage of any liquid leakage.



#### PERFORMANCE ATTRIBUTES

- Anti-fatigue & Anti-Slip.
- Fast installation.
- Easy to clean
- Thermal insulation
- Easy drainage

#### SPECIFICATIONS

- Size: 122x183cm
- Weight- 10mm-32kgs, 14mm – 42kgs, 17mm – 48kgs, 20mm – 56kgs
- Standard Tolerances: Width: +/- 3mm; Length: +/- 3mm Thickness: +/-2mm

#### MATERIAL

- Blend of NR-SBR compound
- Available in Black and other colors upon request

#### TECHNICAL DATA

PROPERTY	TEST METHOD	UNITS	TEST VALUES
Shore Hardness	ASTM D2240-97	Shore A	60±5
Specific Gravity	ASTM D792	g/cm <sup>3</sup>	1.25±0.05
Tensile Strength	ASTM D412-98A	MPa	Min 3
Elongation at Break	ASTM D412-98A	%	Min 280
Compression Set @ 70° / 22hrs	ASTM D395-98	%	35 Max
Abrasion Loss	ASTM D5963	mm <sup>3</sup>	335 Max
Aging Test (70° / 22hrs)	ASTM D573-99		
Hardness Change	ASTM D2240-97	Shore A	+5 Max
Tensile Strength Change	ASTM D412-98a	%	-10 Max
Elongation @ Break Change	ASTM D 412-98a	%	-25 Max
Tear Strength	ASTM D624	KN/m	15 Min

Working Temperature upto 70°C

Good Abrasion Resistance \*The values & properties stated above are carried out in our lab for the component used in the production. However, they do not constitute a guarantee for a specific product feature & do not establish a legal contract

#### CERTIFICATIONS



9001:2015



ASTM INTERNATIONAL  
E648, E492, E2179  
E648, E3152-18



EN1177, EN71



DIN 3763:2022-08



UAE  
صنوعي الإمارات  
MADE IN UAE

#### CONTACT

+971 4 263 2332 | +971 55 325 2253  
inquiry@terrainfloorings.com  
terrainfloorings.com

