

TerraFit® – PERFORMANCE ROLLS

ABOUT

A wide range of rubber rolls available in an extensive collection of colors for use in intensive gym environments. Made of EPDM.



PERFORMANCE ATTRIBUTES

- Compatible with most floor finishes.
- Fast installation.
- Natural elasticity reduces noise.
- Antistatic
- Crack isolation membrane protects ceramic tile, porcelain and stone tile

DIMENSIONS

- Size: 1.2 m x 10 m
- Thickness (mm): 4,6,8,10
- Roll Area: 12m²
- Weight: 4mm = 72 kg
6mm = 107 kg
8mm = 143 kg
10mm = 179 kg

DENSITY

- 1450 - 1550 kg/m³
- 100% EPDM granules.
- Standard Tolerances: Width: ≤ 4mm
Length: +/-10mm-30mm
Thickness: 0.3mm-0.5mm

TECHNICAL DATA

PROPERTY	TEST METHOD	UNITS	TEST VALUES
Hardness	ASTM D 2240-97	Shore A	79
Tensile Strength	ASTM D412-98a	MPa	1.5
Elongation at Break	ASTM D412-98a	%	106
Tear Strength	ASTM D 624	kN/m	11.5
Abrasion Loss 10N Load	ASTM D 5963	mm ³	342
Abrasion Loss 5N Load	ASTM D 5963	mm ³	297
Resilience	ASTM D2632-96	%	32
Specific Gravity	ASTM D297	g/cm ³	1.456

* Note: Our rolls may consist of two combined sections to meet the required length, ensuring quality control

*The values & properties stated above are carried out in our lab for the component used in the production. However, they do not constitute a guarantee for a specific product feature & do not establish a legal contract.

CERTIFICATIONS



CONTACT

+971 4 263 2332 | +971 55 325 2253
inquiry@terrainfloorings.com
terrainfloorings.com

