

TerraFit® – Skirtings

ABOUT

Rubber Skirting adds finishing touch to your walls while providing effective protection. Designed to resist wear and tear, they guard against scuffs, scratches, and impacts, ensuring your walls stay looking good.



PERFORMANCE ATTRIBUTES

- Provides a durable and protective finish at wall-to-floor junctions
- Resistant to impact, abrasion, and everyday wear.
- Easy to clean and maintain.
- Conceals expansion gaps and provides a neat, professional appearance

DIMENSIONS

- Size: 100mmx1000mm
- Thickness (mm): 4,6,8,10
- Width: 100mm
- Roll Area: 10 m²

MATERIAL

- 85% SBR granulated + 15% EPDM granulated in 20+ color combinations.
- Standard Tolerances: Width: +/- 2-3 mm
Thickness: +/-2-3 mm

TECHNICAL DATA

PROPERTY	TEST METHOD	UNITS	TEST VALUES
Hardness	ASTM D 2240-97	Shore A	70
Tensile Strength	ASTM D412-98a	MPa	2.4
Elongation at Break	ASTM D412-98a	%	176
Tear Strength	ASTM D 624	kN/m	12
Abrasion Loss 10N Load	ASTM D 5963	mm ²	95
Resilience	ASTM D2632-96	%	35
Specific Gravity	ASTM D297	g/cm ³	1.111

* Note: Our rolls may consist of two combined sections to meet the required length, ensuring quality control

*The values & properties stated above are carried out in our lab for the component used in the production. However, they do not constitute a guarantee for a specific product feature & do not establish a legal contract.

CERTIFICATIONS



CONTACT

+971 4 263 2332 | +971 55 325 2253
inquiry@terrainfloorings.com
terrainfloorings.com



v1